Navilock Multiband GNSS GALILEO GPS LTE UMTS GSM SMA Antenna omnidirectional roof mount outdoor

Popis

This Navilock multi-band antenna has three physically separate transmitting and receiving units. The GNSS patch antenna receives the signals of the Global Navigation Satellite System GALILEO GPS. Two PIFA antennas, respectively, for LTE and GSM / UMTS are responsible for sending and receiving in these areas.
Due to its outdoor features, the multiband antenna is well suitable for usage in harsh areas such as transportation, forestry, agriculture, construction and in the maritime sector. It is waterproof, shock resistant and can be used in the extended temperature range.



Číslo produktu 12457

EAN: 4043619124572

Země původu: China

Balení: White Box

Specifikace

- Connectors: 3 x SMA plug

- GNSS:
  Frequency range:
  GPS: L1, 1.57542 GHz
  GALILEO: E1, 1,57542 GHz
  Antenna gain: 4 dBi
  VSWR: 2.5
  Impedance: 50 Ohm
  Polarisation: RHCP

- LNA GPS:
  Frequency range:
  GPS: L1, 1.57542 GHz
  GALILEO: E1, 1,57542 GHz
  Gain: 28 dBi
  Voltage: 2.2 - 5.0 V

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

Current: 5 - 15 mA
VSWR: 2.0
Impedance: 50 Ohm
Cable category: coaxial
Cable type: RG-174
Cable attenuation:
1.5 dB @ 1.5 GHz per meter
Cable diameter: ca. 2.7 mm

- LTE:
  Frequency range:
  0.698 - 0.960 GHz
  1.710 - 2.700 GHz
  LTE Band: 1-10/ 12-20/ 23/ 25-30/ 33-41
  GSM / UMTS / LoRa 868 MHz, 915 MHz / ZigBee / Z-Wave / WLAN 2.4 GHz / Bluetooth
  Antenna gain: 3 dBi
  Impedance: 50 Ohm
  Polarisation: linear
  VSWR: 2.5
  Cable category: coaxial
  Cable type: RG-58/U
  Cable attenuation:
  0.6 dBi @ 1 GHz per meter
  Cable diameter: ca. 4.95 mm

- GSM UMTS:
  Frequency range:
  0.824 - 0.960 GHz
  1.710 - 2.170 GHz
  GSM / UMTS / Z-Wave
  Antenna gain: 3 dBi
  Impedance: 50 Ohm
  Polarisation: linear
  VSWR: 2.5
  Cable category: coaxial
  Cable type: RG-58/U
  Cable attenuation:
  0.6 dBi @ 1 GHz per meter
  Cable diameter: ca. 4.95 mm
- Operating temperature: -40 °C ~ 85 °C
- Housing material: ABS
- Protection class: IP67
- Screw assembly:

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

Hole diameter: 30 mm

- Colour: black
- Dimension (ØxH): ca. 143.6 x 65 mm
- Cable color: black
- Cable length: ca. 3 m

Systémové požadavky

- Device with free SMA connectors

Obsah balení


- Multiband antenna
- Nut


© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.


Příslušenství















































© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

General

Mounting type:	design mounting
Protection category:	IP67
Suitable for outdoor:	Yes

Interface

konektor:	3 x SMA

Technical characteristics

Operating voltage:	2.2 - 5.0 V
Frequency range:	824 MHz - 960 MHz 1.57542 GHz 1.71 - 2.17 GHz 1.71 GHz - 2.70 GHz 698 MHz - 960 MHz
Gain:	4 dBi 28 dBi 3 dBi
Impedance:	50 Ω
Polarisation:	RHCP linear vertical
Power handling:	5 W 1 W
Current consumption:	5 - 15 mA
VSWR:	2,5 2,0

Physical characteristics

Pouzdro barva:	černá
Materiál pouzdra:	ABS
Weight:	1,2 kg

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

Cable category:	coaxial cable
Cable type:	RG-174 RG-58 U
Cable attenuation:	1.5 dB @ 1.5 GHz per meter RG-174 0.6 dB @ 1.0 GHz per meter RG-58/U
Barva kabelu:	černá
Délka kabelu:	3 m (incl. connectors)
Diameter:	143.6 mm
Height:	6.5 cm

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.