

Navilock Multiband GNSS GALILEO GPS LTE UMTS GSM SMA Antenna omnidirectional roof mount outdoor

Opis

This Navilock multi-band antenna has three physically separate transmitting and receiving units. The GNSS patch antenna receives the signals of the Global Navigation Satellite System GALILEO GPS. Two PIFA antennas, respectively, for LTE and GSM / UMTS are responsible for sending and receiving in these areas.

Due to its outdoor features, the multiband antenna is well suitable for usage in harsh areas such as transportation, forestry, agriculture, construction and in the maritime sector. It is waterproof, shock resistant and can be used in the extended temperature range.



Numer artykułu 12457

EAN: 4043619124572

Kraj pochodzenia: China

Opakowanie: White Box

Specyfikacja

- Connectors: 3 x SMA plug
- GNSS:
 - Frequency range:
 - GPS: L1, 1.57542 GHz
 - GALILEO: E1, 1,57542 GHz
 - Antenna gain: 4 dBi
 - VSWR: 2.5
 - Impedance: 50 Ohm
 - Polarisation: RHCP
- LNA GPS:
 - Frequency range:
 - GPS: L1, 1.57542 GHz
 - GALILEO: E1, 1,57542 GHz
 - Gain: 28 dBi
 - Voltage: 2.2 - 5.0 V

Current: 5 - 15 mA

VSWR: 2.0

Impedance: 50 Ohm

Cable category: coaxial

Cable type: RG-174

Cable attenuation:

1.5 dB @ 1.5 GHz per meter

Cable diameter: ca. 2.7 mm

- LTE:

Frequency range:

0.698 - 0.960 GHz

1.710 - 2.700 GHz

LTE Band: 1-10/ 12-20/ 23/ 25-30/ 33-41

GSM / UMTS / LoRa 868 MHz, 915 MHz / ZigBee / Z-Wave / WLAN 2.4 GHz / Bluetooth

Antenna gain: 3 dBi

Impedance: 50 Ohm

Polarisation: linear

VSWR: 2.5

Cable category: coaxial

Cable type: RG-58/U

Cable attenuation:

0.6 dBi @ 1 GHz per meter

Cable diameter: ca. 4.95 mm

- GSM UMTS:

Frequency range:

0.824 - 0.960 GHz

1.710 - 2.170 GHz

GSM / UMTS / Z-Wave

Antenna gain: 3 dBi

Impedance: 50 Ohm

Polarisation: linear

VSWR: 2.5

Cable category: coaxial

Cable type: RG-58/U

Cable attenuation:

0.6 dBi @ 1 GHz per meter

Cable diameter: ca. 4.95 mm

- Operating temperature: -40°C ~ 85°C
- Housing material: ABS
- Protection class: IP67
- Screw assembly:

Hole diameter: 30 mm

- Colour: black
- Dimension (ØxH): ca. 143.6 x 65 mm
- Cable color: black
- Cable length: ca. 3 m












Wymagania systemowe

- Device with free SMA connectors


Zawartość opakowania

- Multiband antenna
- Nut


Zdjęcia




1710 MHz




1990 MHz




2170 MHz



XZ-plane Free Space @1575.42MHz



YZ-plane Free Space @1575.42MHz



General

Mounting type:	design mounting
Protection category:	IP67
Suitable for outdoor:	Tak

Interface

złącze :	3 x SMA
----------	---------

Technical characteristics

Operating voltage:	2.2 - 5.0 V
Frequency range:	824 MHz - 960 MHz 1.57542 GHz 1.71 - 2.17 GHz 1.71 GHz - 2.70 GHz 698 MHz - 960 MHz
Gain:	4 dBi 28 dBi 3 dBi
Impedancja:	50 Ω
Polarisation:	RHCP linear vertical
Power handling:	5 W 1 W
Current consumption:	5 - 15 mA
VSWR:	2,5 2,0

Physical characteristics

Obudowa kolor:	czarny
Materiał obudowy:	ABS
Weight:	1,2 kg

Cable category:	coaxial cable
Cable type:	RG-174 RG-58 U
Cable attenuation:	1.5 dB @ 1.5 GHz per meter RG-174 0.6 dB @ 1.0 GHz per meter RG-58/U
Kolor przewodu:	czarny
Długość kabla:	3 m (incl. connectors)
Diameter:	143.6 mm
Height:	6.5 cm