Navilock NL-404P serial MD6 GPS / Galileo Receiver Outdoor

Popis

The GPS receiver with u-blox 5 SuperSence® chipset can receive WAAS and EGNOS data besides GPS. The u-blox 5 chipset enables you to receive the European navigation system Galileo in the future. The MD6 universal connector enables the connection of optional USB or serial connecting cables. The NL-404P GPS receiver can be installed onto different vehicle roofs (car, truck, bus etc.) by using the included installation material. Thus it can perfectly fit into the vehicle concept, due to its design.



Číslo produktu 60096

EAN: 4043619600960

Země původu: Taiwan, Republic Of China

Balení: Kartonová krabice

Specifikace

- u-blox 5 GPS & GALILEO SuperSence® high performance chipset
- GPS receiver with MD6 Navilock plug
  (USB or serial cable are optional available)
- Accepts the signals of up to 50 satellites at the same time
- High Sensitive (Tracking sensitivity: -160 dBm)
- Internal patch antenna
- Supports AssistNow Offline (14 days Almanac data)
- Supports WAAS, EGNOS and MSAS
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- Extreme short TTFF (Time To First Fix) also with low signal
- Water-proof housing (**IPX7**)
- Central fastening screw thread with cable leading from the middle
- 38400 Baud (flexible)
- UP-DATE Rate: up to 4 Hz
- Dimension: 62 mm x 21 mm
- Cable length: 5 m
- Operating temperature: -20°C to 60°C

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

Systémové požadavky

- Windows 2000/XP/Vista/7/CE, Windows Mobile 4/5/6, Mac, Linux 2.4.x
- MD6 connection cable

Obsah balení

- NL-404P Receiver
- Installation material
- CD ROM

Příslušenství








© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.