

Navilock NL-403P serial MD6 GPS / Galileo Receiver

Opis

The GPS Receiver based on u-blox 5 SuperSense® chipset has a built-in antenna for high sensitivity. Besides GPS, this u-blox 5 chipset enables you in future to receive also Galileo, the european navigationsystem.

The MD6 universal connector enables the connection of optional USB or serial connecting cables. You can use this GPS Receiver with a Car PC or a Notebook and a suitable routing software for navigation.



Numer artykułu 60109

EAN: 4043619601097

Kraj pochodzenia:
Taiwan, Republic of
China

Opakowanie: Retail Box

Specyfikacja

- u-blox 5 GPS & GALILEO SuperSense® high performance chipset
- GPS receiver with MD6 Navilock plug
(USB or serial cable are optional available)
- Accepts the signals of up to 50 satellites at the same time
- Supports DGPS, WAAS, EGNOS and MSAS
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- Supports AGPS
- 38400 Baud (flexible)
- UP-DATE Rate: up to 4 Hz
- IPX6 protection class
- Magnatic, non-slip on the bottom
- Operating temperature -10°C bis +60°C
- Cold start in about 30 sec.
- Warm start in about 25 sec.
- Hot start in about 1 sec.
- Cable length: 1.5 meter
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm

Wymagania systemowe

- Windows 98SE/ME/2000/XP/Vista/7, Windows Mobile 2003/5/6, Linux, Mac
- MD6 connection cable

Zawartość opakowania

- NL-403P Receiver
- Driver CD
- User manual on CD ROM

Zdjęcia

