

Navilock NL-522ETTL Skytraq GPS Engine Module

Opis

The GPS Engine Board Module is due to its compact design and low power consumption ideal for any application in small systems. The module is based on the SkyTraq-638 high performance chipset which features high sensitivity and a very fast Time To First Fix, also with a low signal. Due to its high update rate the module is perfect for vehicles, planes and boats which move with a high speed.



Specyfikacja

- Chipset: SkyTraq-638
- Interface: RS232 / TTL
- Average power consumption: 40 mA
- Voltage: 3.5 V ~ 5.5 V
- Update rate: 20 Hz
- Operating temperature: - 40 °C to 85 °C (Battery: - 10 °C ~ 60 °C)
- Baudrate: 115200 bps
- Sensitivity: - 159 dBm (tracking)
- Hot start: • Warm start: • Cold start: • 1 x LED for Satfix
- 6 pin connector
- Dimension (LxWxH): 30 mm x 30 mm x 6,4 mm

Wymagania systemowe

- Windows XP/XP-64/Vista/Vista-64/7/7-64

Zawartość opakowania

- GPS module
- CD-ROM

Numer artykułu 60426

EAN: 4043619604265

Kraj pochodzenia:

Opakowanie: Poly bag



Zdjęcia

