

Navilock NL-200AA SMA GPS Antenna high gain 15 m

Opis

This GPS antenna by Navilock can be used with an existing GPS receiver or PNA with SMA connection. Improvement of reception will be provided by placing the antenna, e.g. on the hat rack or car roof, where it has a better or free view to the sky. The antenna is waterproof and can temporary also be used outside of the vehicle.



15 m

Numer artykułu 60521

EAN: 4043619605217

Kraj pochodzenia: China

Opakowanie: Torba na zamek błyskawiczny

Specyfikacja

- External active additional antenna for GPS receiver
- Internal patchantenna: 25 x 25 x 4 mm
- Ground plate metal: 40 x 40 mm (PCB)
- Frequency range: 1575.42 MHz +/- 1.02 MHz
- VSWR: 1.5 typ.
- Gain: 5 dBic (7 cm x 7cm ground plane)
- Polarisation: RHCP

LNA

- Gain: 37 dB
- Voltage: 3.0 ~ 5.0 V
- VSWR: 1.5 typ.
- Noise figure: 1.5 @ 25°C +/- 10 °C
- SMA plug
- Cable type: RG-174
- Impedance: 50 Ohm,
- Cable length: 15 m
- Cable attenuation: 11.40 dB
- Dimension: 50.6 x 50.6 x 15.1 mm
- Current: typ. 25.5 mA @ 5.0 V
- IPX-6
- magnetical bottom

Wymagania systemowe

- GPS Empfänger mit SMA Buchse

Zawartość opakowania

- GPS antenna

Zdjęcia

