

Navilock NL-202AA GNSS GALILEO GPS SMA Plug Antenna High Gain 5 m outdoor

Opis

This GPS antenna by Navilock can be used with an existing GPS receiver or PNA with SMA connection. Improvement of reception will be provided by placing the antenna, e.g. on the hat rack or car roof, where it has a better or free view to the sky. The antenna is waterproof and can temporary also be used outside of the vehicle.



5 m

Numer artykułu 60524

EAN: 4043619605248

Kraj pochodzenia: China

Opakowanie: Torba na zamek błyskawiczny

Specyfikacja

- External active additional antenna for GPS receiver
- internal patchantenna: 25 x 25 x 4 mm
- Ground plate metal: 40 x 40 mm (PCB)
- Frequency range: 1575.42 MHz +/- 1.02 MHz
- Bandwidth > 10MHz
- VSWR: 1.5 typ.
- Gain: 5 dBic (7 cm x 7 cm ground plane)
- Polarisation: RHCP

LNA

- Gain: 37 dB
- Voltage: 3.0 ~ 5.0 V
- VSWR: 1.5 typ.
- Noise figure: 1.5 @ 25°C +/- 10 °C
- SMA plug: brass gold plated
- SMA contact: gold plated
- Cable type: RG-174
- Impedance: 50 Ohm
- Cable length: 5 m
- Cable attenuation: 5.70 dB
- Dimension: ca. 50.6 x 50.6 x 15.1 mm
- Current: typ. 25.5 mA @ 5.0 V
- IPX-6
- Magnetical bottom

- Working temperature: -40 °C ~ 80°C
-

Zawartość opakowania

- GPS antenna
-

Zdjęcia

