
Navilock GNS602 MT3339 TTL GPS Engine Module PPS

Description

This engine module concerns a complete GNSS receiver and including a patch antenna.



Item no. 60546

EAN: 4037735104662

Country of origin: GERMANY

Package: Retail Box

Special features

- Logger Function
- PPS (Puls per Second)
- Up to 10Hz

Specification

• Chipset: MT3339
• N navigation sensitivity -165 dB
• TTL 3,3V
• Concurrent receipt 22/Tracking, 66/Acquisition Satellites
• Active interference cancellation (MTAIC)
• NMEA: GPRMC, GPGSA, GPGSV, GPGGA, GPVTG
• SBAS (EGNOS, WAAS, GAGAN, MSAS, QZSS)

• Logger Function 128 kBytes (16h)

• Position accuracy 2,50 m
• PPS (Puls per Second)
• Update Rate 1/s , 9600 bps (default)
• Real time clock intern (RTC)
• A-GPS (Internet required)
• TTFF (Time to first FIX)
Cold 35s

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Warm 34s
Hot 1s

- C[current consumption] tracking: 20 mA @ 3,30 V
- Fo[m factor]: 16,00 x 16,00 x 5,20 mm
- [Patch antenna]5,20 x 3,70 x 0,70 mm
- Operating tempature: -40 °C ~ 85°C

System requirements

- No system required

Package content

- CD
- GNSS module

Images





© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.