# Navilock NL-662U USB 2.0 GLONASS GPS Receiver u-blox 6

## Description

The USB 2.0 receiver based on u-blox 6 chipset has a built-in antenna and uses the Russian satellite system GLONASS. It can be set to GPS. You can use this receiver with a notebook and a suitable routing software for navigation.



**Item no. 61973**

EAN: 4043619619733

Country of origin: Taiwan, Republic Of China

Package: Retail Box

## Specification

- u-blox 6 chipset UBX-G6000-BT
- GLONASS GPS receiver with USB 2.0 type-A connector
- Setting option for GPS / QZSS
- Internal patch antenna
- Frequency: L1, 1602 MH
- Accepts the signals of up to 50 satellites at the same time
- Supports AssistNow®
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG, GLL
- Auto Baud Rate up to 115200 bps (default 9600 bps)
- Update rate: up to 1 Hz
- Datum: PZ90.2
- Sensibility max. –158 dBm
- IPX6 protection class
- Magnetic, non-slip on the bottom
- LED-indicator for reception status
- Operating temperature: -20 °C to +65 °C
- Cold start in ca. 38 seconds
- Hot start in ca. 3 seconds

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Cable length: 1.5 meter
- Positioning accuracy: 5 - 9 m (> 10 m outside Russia)
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm

## System requirements

- Windows 98SE/ME/2000/XP/Vista/7/8, Linux ex Kernel 2.6
- PC or Notebook with a free USB Port

## Package content

- NL-662U receiver
- Driver CD
- User manual on CD ROM

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.