# Navilock Engine Module mini PCIe GPS TTL 4800 u-blox 6 Navilock

## Description

This high-quality GNSS module provides all the functions of a GNSS receiver, and can be easily integrated into your systems.



**Item no. 95924**

EAN: 4043619959242

Country of origin:
TAIWAN, REPUBLIC OF CHINA

Package:

## Specification

- Chipset u-blox 6
- Sensitivity: -160dBm tracking + navigation
- Update rate: 1 - 5 Hz
- MiniPCI Express TTL 4800bps Pin 45 RXD, Pin 47 TXD
- GGA, GSA, GSV, RMC, VTG, TXT
- WAAS, EGNOS, MSAS, GAGAN
- Voltage: 3.0 ~ 3.6 V (typ. 3,3 V)
- RF miniature coaxial connector I-PEX Inc., MHF/U.FL compatible
- Operating temperature:
  -40 °C ~ 85° C without battery
  -20 °C ~ 60 °C with battery
- Current: 50mA
- Dimensions: 26.8 x 30.0 x 2.8 mm

## Package content

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- GNSS module

## Images





© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.