

# Delock USB Charger USB Type-C™ PD 3.0 and USB Type-A with 20 W + 12 W

## Description

This USB charger by Delock can be used to charge two USB devices. One port is equipped with a **USB Type-C™ Power Delivery (PD)**, thereby supported devices can be charged with **up to 20 watt**.

In addition, one **USB Type-A** connector with a voltage of 5 V, and max. **12 watt** power for other mobile devices is available.



**Item no. 41455**

EAN: 4043619414550

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB Type-C™ female
  - 1 x USB Type-A female
  - 1 x plug CEE 7/16
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.0 A
- Output:
  - USB-C™ 5.0 V 3.0 A, 9.0 V 2.22 A (20.0 W)
  - USB-A 5.0 V 2.4 A (12.0 W)
- Output power: max. 32.0 W total
- Average active efficiency 85.51 %
- Efficiency at low load (10 %) 79.77 %
- No-load power consumption 0.115 W
- Overload protection
- Over current protection
- Overheating protection
- Short circuit protection
- Colour: black
- Dimensions without plug (LxWxH): ca. 59.5 x 59.5 x 27.5 mm

---

## Package content

- USB Charger
- User manual

---

## Images



## Physical characteristics

|                 |         |
|-----------------|---------|
| Housing colour: | black   |
| Length:         | 59,4 mm |
| Width:          | 59.4 mm |
| Height:         | 27.5 mm |

## Power supply

|            |   |
|------------|---|
| Input:     | AC 100 - 240 V / 50 - 60 Hz / 1.0 A             |
| Output:    | 5.0 V / 3.0 A<br>5 V / 2.4 A<br>9,0 V / 2,0 A   |
| Connector: | 1 x USB Type-C™ female<br>1 x USB Type-A female |