

Navilock NL-601US USB 2.0 GPS Receiver

Description

The USB GPS Receiver based on u-blox 6 chipset has a built-in antenna for high sensitivity. You can use this GPS Receiver with a notebook and a suitable routing software for navigation. Due to its compact design it is the ideal companion on every tour.



Specification

- u-blox 6 GPS SuperSense® high performance chipset
 - Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz
 - Accepts the signals of up to 50 satellites at the same time
 - Supports AGPS, WAAS, EGNOS and MSAS
 - Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
 - USB specification 2.0
 - Baud Rate up to 115200
 - UP-DATE Rate: up to 5 Hz
 - Sensibility max. -162dBm
 - LED-indicator for GPS-status
 - Operating temperature: -20 °C to +60 °C
 - Cold start in about 25 sec.
 - Hot start in about 1 sec.
 - Positioning accuracy: 2.5 m CEP (Circular Error Probable) and 2 m CEP with SBAS
 - Dimension (LxWxH): 65.5 mm x 23 mm x 11 mm
- Microsoft sensor and location platform ([internet](#))

System requirements

- Linux ex Kernel 2.6, Windows 98SE/ME/2000/XP/Vista/7/8/10, Windows Mobile 2003/5/6
- PC or Notebook with a free USB Port
- For devices with OTG function and optional OTG adapter: Windows 10

Package content

- USB GPS receiver
- USB extension cable
- Driver CD
- User manual on CD ROM

Item no. 60123

EAN: 4043619601233

Country of origin: Taiwan, Republic of China

Package: Retail Box



Images



