

# Navilock NL-522ETTL Skytraq GPS Engine Module

## Opis

The GPS Engine Board Module is due to its compact design and low power consumption ideal for any application in small systems. The module is based on the SkyTraq-638 high performance chipset which features high sensitivity and a very fast Time To First Fix, also with a low signal. Due to its high update rate the module is perfect for vehicles, planes and boats which move with a high speed.



## Specyfikacja

- Chipset: SkyTraq-638
- Interface: RS232 / TTL
- Average power consumption: 40 mA
- Voltage: 3.5 V ~ 5.5 V
- Update rate: 20 Hz
- Operating temperature: - 40 °C to 85 °C (Battery: - 10 °C ~ 60 °C)
- Baudrate: 115200 bps
- Sensitivity: - 159 dBm (tracking)
- Hot start: • Warm start: • Cold start: • 1 x LED for Satfix
- 6 pin connector
- Dimension (LxWxH): 30 mm x 30 mm x 6,4 mm


## Wymagania systemowe

- Windows XP/XP-64/Vista/Vista-64/7/7-64

## Zawartość opakowania

- GPS module
- CD-ROM

## Zdjęcia



## Numer artykułu 60426

EAN: 4043619604265

Kraj pochodzenia:

Opakowanie: Poly bag

