Navilock NL-200AA SMA GPS Antenna high gain 15 m

Descripción

This GPS antenna by Navilock can be used with an existing GPS receiver or PNA with SMA connection. Improvement of reception will be provided by placing the antenna, e.g. on the hat rack or car roof, where it has a better or free view to the sky. The antenna is waterproof and can temporary also be used outside of the vehicle.



15 m

Número de elemento 60521

EAN: 4043619605217

Pais de origen: China

Paquete: Bolsa de plástico con cremallera

Especificación técnica

• External active additional antenna for GPS receiver
• Internal patchantenna: 25 x 25 x 4 mm
• Ground plate metal: 40 x 40 mm (PCB)
• Frequency range: 1575.42 MHz +/- 1.02 MHz
• VSWR: 1.5 typ.
• Gain: 5 dBic (7 cm x 7cm ground plane)
• Polarisation: RHCP
LNA
• Gain: 37 dB
• Voltage: 3.0 ~ 5.0 V
• VSWR: 1.5 typ.
• Noise figure: 1.5 @ 25°C +/- 10 °C
• SMA plug
• Cable type: RG-174
• Impedance: 50 Ohm,
• Cable length: 15 m
• Cable attenuation: 11.40 dB
• Dimension: 50.6 x 50.6 x 15.1 mm
• Current: typ. 25.5 mA @ 5.0 V
• IPX-6
• magnetical bottom

Requisitos del sistema

- GPS Empfänger mit SMA Buchse

© 2024 by Navilock. Todos los nombres y símbolos aquí mencionados son propiedad de sus respectivos productores. Exceptuando errores, errores de impresión y cambios.

Contenido del paquete

- GPS antenna

Image



© 2024 by Navilock. Todos los nombres y símbolos aquí mencionados son propiedad de sus respectivos productores. Exceptuando errores, errores de impresión y cambios.