Navilock NL-303P serial MD6 GPS Receiver

Popis

The PDA GPS Receiver based on SiRFstarIII™ Chipset has a built-in antenna for high sensitivity.
The MD6 universal connector enables the connection of optional USB or serial connecting cables. You can use this GPS Receiver on a Notebook or PDA with suitable routing software for navigation.



Číslo produktu 61423

EAN: 4043619614233

Země původu: Taiwan, Republic Of China

Balení: Kartonová krabice

Speciální vlastnosti

Please note that the SiRFstarIII chipset used here has reached the end of its production cycle. This receiver is delisted in the next few weeks.

Specifikace

- SiRFstarIII™ high performance and low power chipset
- GPS receiver with MD6 Navilock plug
  (USB or serial cable are optional available)
- Accepts the signals of up to 20 satellites at the same time
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, GLL and VTG
- 4800 – 38400 Baud
- Waterproof housing
- Magnatic, non-slip on the bottom
- LED-indicator for GPS-status
- Cold start in about 42 sec.
- Warm start in about 38 sec.
- Hot start in about 1 sec.
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm
- Cable lenght: 1.50 m

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

Systémové požadavky

- Windows CE/98/ME/2000/XP/Vista/7
- MD6 connection cable

Obsah balení

- PDA GPS Receiver
- Driver CD
- User manual

Příslušenství



© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.