Navilock NL-622MP serial MD6 GPS Receiver Outdoor Marine

Popis

The GPS receiver with u-blox 6 SuperSence® chipset can receive WAAS and EGNOS data besides GPS. The MD6 universal connector enables the connection of optional USB or serial connecting cables. The NL-622MP GPS receiver is especially designed for installation on a white ground (boat, camper, bus etc.) It is unremarkable and fits into the vehicle concept due to its housing design.



Číslo produktu 61843

EAN: 4043619618439

Země původu: Taiwan, Republic of China

Balení: Kartonová krabice

Specifikace

- u-blox 6 GPS SuperSense® high performance chipset
- GPS receiver with MD6 Navilock plug (USB or serial cable are optional available)
- Internal patch antenna
- Central fastening screw thread with cable leading from the middle
- Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz
- Accepts the signals of up to 50 satellites at the same time
- Supports AssistNow Offline (14 days Almanac data), AGPS, WAAS, EGNOS, MSAS, NMEA 0183 protocols: GGA, GSA, GSV, RMC, VTG
- Baud rate: 9600 (up to 115200)
- Update rate: up to 5 Hz
- Sensibility max. −162 dBm
- Water-proof housing (**IPX7**)
- Operating temperature: -20 °C ~ 60 °C
- Cold start in about 25 sec.
- Hot start in about 1 sec.
- Cable length: 5 m

© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.

- Positioning accuracy: 2.5 m CEP (Circular Error Probable) and 2 m CEP with SBAS
- Dimension: 62 mm x 21 mm

Systémové požadavky

- Linux ex Kernel 2.6, Mac, Windows 98SE/ME/2000/XP/Vista/7/8, Windows Mobile 2003/5/6, Android ex V2.1
- MD6 connection cable

Obsah balení

- NL-622MP receiver
- Installation material
- CD ROM

Příslušenství



© 2024 by Navilock. Všechny názvy a symboly zde uvedené jsou vlastnictvím výrobce.
Tiskové chyby, změny a chyby v datech vyhrazeny.