

Navilock NL-443P MD6 GPS Receiver SiRFstarIV™

Description

The GPS Receiver based on SiRFstarIV™ chipset has a built-in antenna for high sensitivity. The MD6 universal connector enables the connection of optional USB or serial connecting cables. You can use this GPS Receiver with a Car PC or a notebook and a suitable routing software for navigation.



Item no. 61995

EAN: 4043619619955

Country of origin: Taiwan,
Republic Of China

Package: Retail Box

Specification

- SiRFstarIV™ GSD4e chipset
- GPS receiver with MD6 Navilock connector
(USB or serial cable are optional available)
- Frequency: L1, 1575.42 MHz, C/A Code: 1.023 MHz
- Accepts the signals of up to 48 satellites at the same time
- Supports WAAS, EGNOS and MSAS
- Supports NMEA 0183 V3.0 protocols: GGA, GSA, GSV, RMC, VTG, GLL v2.2 (VTG and GLL are optional)
- 4800 ~ 38.400 baud rate
- Update rate: 1 Hz
- Datum: WGS-84
- Sensibility max. -163 dBm
- IPX6 protection class
- Magnatic, non-slip on the bottom
- LED-indicator for GPS-status
- Operating temperature: -20 °C to +65 °C
- Cold start in about 35 sec.
- Hot start in about 1 sec.
- Positioning accuracy: < 2.5 m 2D RMS SBAS Enable

- Dimension (LxWxH): 65 mm x 45 mm x 22 mm

System requirements

- Windows 2000/XP/Vista/7/8,
Windows Mobile 2003/5/6
Linux ab Kernel 2.6,
Mac OS 10.6.x, 10.7.x
- MD6 connection cable

Package content

- NL-443P receiver
- User manual on CD ROM

Images

