

# Navilock Connection Cable MD6 female serial > 3,5 mm 4 pin stereo jack male 90° TTL (5 V) 52 cm

## Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to TTL 5 V signals. Compatible with TTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

## Specification

- Connectors:  
1 x MD6 female >  
1 x 3.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 5 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

## System requirements

- A Navilock serial MD6 GNSS receiver

## Package content


- Connection cable for GNSS receiver
- Navilock support CD

## Item no. 62880


EAN: 4043619628803

Country of origin: Taiwan, Republic of China

Package: Poly bag



## Images



General	
Style:	<b>standard</b> angled 90°
Interface	
connector:	<b>standard</b> 1 x MD6 jack
Connector 1:	<b>standard</b> 1 x 3.5 mm 3 pin stereo jack male
Technical characteristics	
Chipset:	<b>standard</b> ASIX ZT3221LEEY
Voltage:	<b>standard</b> 5 V
Physical characteristics	
Cable colour:	<b>standard</b> black
Cable length incl. connector:	<b>standard</b> 52 cm