



# Navilock Connection Cable M8 female serial waterproof > 5 x open wire TTL (5 V) 1.2 m

## Description

The waterproof connection cable by Navilock converts the serial signals for all M8 receivers to TTL 5 V signals. Compatible with TTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 1,2 m

**Item no. 62892**

EAN: 4043619628926

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x M8 female >
  - 1 x 5 pin open wire
- Chipset: ASIX ZT3221LEEY
- Cable gauge: 28 AWG
- Voltage: 5 V
- Waterproof
- Cable colour: black
- Cable length incl. connectors: ca. 1.2 m

## System requirements

- A Navilock serial M8 GNSS receiver

## Package content

- Connection cable for M8 GNSS receiver
  - Navilock support CD
- 

## Images



## General

Protection category:	waterproof
----------------------	------------

## Interface

connector:	1 x M8 female
Connector 1:	1 x open wire

## Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	5 V

## Physical characteristics

Cable colour:	black
Cable length incl. connector:	1.20 m