

Navilock Connection Cable MD6 female serial > 2.5 mm 4 pin stereo jack male 90° LVTTL (3.3 V) 52 cm

Description

The connection cable by Navilock converts the serial signals universally for all MD6 receivers to LVTTL 3.3 V signals. Compatible with LVTTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

Specification

- Connectors:
1 x MD6 female >
1 x 2.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: bidirectional
- Voltage: 3.3 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

System requirements

- A Navilock serial MD6 GNSS receiver

Package content


- Connection cable for GNSS receiver
- Navilock support CD

Item no. 62924

EAN: 4043619629244

Country of origin: Taiwan, Republic of China

Package: Poly bag



Images



General

Style: **standard**
angled 90°

Interface

connector: **standard**
1 x MD6 jack

Connector 1: **standard**
1 x 2.5 mm 4 pin stereo jack male

Technical characteristics

Chipset: **standard**
ASIX ZT3221LEEY

Voltage: **standard**
3.3 V

Physical characteristics

Cable colour: **standard**
black

Cable length incl. connector: **standard**
52 cm