

# Navilock USB Charger 1 x USB Type-C™ PD + 3 x USB Type-A 60 W + 12 W

## Description

This USB Power Delivery (PD) charger by Navilock can be used to charge laptops with USB Type-C™ connector. It provides various voltages from 5 V to 20 V and power up to 60 Watt. In addition, 3 USB Type-A 5 V connectors with intelligent charging technology are available for conventional devices.



**Item no. 62952**

EAN: 4043619629527

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB Type-C™ female
  - 3 x USB Type-A female
  - 1 x IEC-60320-C8 connector
- Input:
  - AC 100 ~ 240 V / 50 ~ 60 Hz / 1.5 A
- Output:
  - USB Type-C™ 5.0 V / 9.0 V / 12.0 V / 15.0 V / 20.0 V 3.0 A (max. 60.0 W)
  - USB Type-A 5.0 V / 2.4 A (max. 12.0 W)
- Output power: max. 72.0 W total
- Average active efficiency 84.49 % (5.0 V / 3.0 A + 5.0 V / 2.4 A)
- Average active efficiency 88.57 % (20.0 V / 3.0 A + 5.0 V / 2.4 A)
- Efficiency at low load (10 %) 78.99 % (5.0 V / 3.0 A + 5.0 V / 2.4 A)
- Efficiency at low load (10 %) 80.53 % (20.0 V / 3.0 A + 5.0 V / 2.4 A)
- No-load power consumption 0.187 W
- Overload protection
- Over current protection
- Overheating protection
- Short circuit protection

- Operating temperature: 0 °C ~ 40 °C
- Storage temperature: -20 °C ~ 80 °C
- Colour: white
- Dimensions (LxWxH): ca. 91.0 x 75.0 x 27.5 mm

---

## System requirements

- Device with a free USB port
- Connection cables


---

## Package content

- USB charging station
- Power cord, length ca. 1.2 m
- User manual

---

## Images



## Physical characteristics

Housing colour:	white
-----------------	-------

## Power supply

Type:	Power supply with IEC connector
Input:	AC 100 - 240 V / 50 - 60 Hz / 1,5 A
Output:	5.0 V / 3.0 A 5 V / 2.4 A 9.0 V / 3.0 A 12.0 V / 3.0 A 15.0 V / 3.0 A 20.0 V / 3.0 A
Connector:	1 x USB Type-C™ female 3 x USB type-A female